

Manual gate 1000 mm



NTM MGM 1000 • NTM MGL 1000 • NTM MGXL 1000

By manual lifting the conveyor section, access is gained to the rear of the line.

Standard features

- Conveyor width adjustment using hand crank.
- Ergonomic air pressure supported opening and closing.
- Locking device to avoid opening during PCB transfer.
- Controlled by PLC.
- CE certified.


Technical specifications

Transfer height:	950 mm ± 25 mm*
Colour:	RAL 9002*
Flow direction:	Left to right*
Fixed rail:	Front*
Machine interface:	SMEMA*
Conveyor concept:	ESD belt
Belt speed:	14 m/min.
PCB edge support:	3 mm
Components clearance:	Top 30 mm, bottom 30 mm
Power supply:	230 VAC/50 Hz/1 Ph
Power consumption:	100 VA max.
Passageway:	600 mm
Air supply:	4-6 bar
Air consumption:	35 ltr/lift max.
	* or specify

Options

- Machine length 1500 mm, passageway of 990 mm
- Electrical conveyor width adjustment
- Automatic conveyor width adjustment
- Variable speed per segment
- Dual speed per segment
- Inspect function
- Top cover

Other options available on request



	NTM MGM 1000	NTM MGL 1000	NTM MGXL 1000
Machine dimensions (l x w x h)	1000 x 790 x 1100 mm	1000 x 920 x 1100 mm	1000 x 970 x 1100 mm
Weight	90 kg	100 kg	110 kg
PCB length	80 mm - 457 mm	80 mm - 457 mm	80 mm - 460 mm*
PCB width	50 mm - 250 mm	50 mm - 407 mm	50 mm - 460 mm*
Fixed rail to front dimension (A)	194 mm	194 mm	194 mm

* or specify