

**This unit is used to invert/flip PCB's (180°) for 'double-sided' process.**



### Standard features


- Rotation using pneumatic cylinder.
- Conveyor width adjustment using hand crank.
- Pneumatic stopper to keep PCB in position during inverting.
- Controlled by PLC.
- By-pass mode selectable.
- CE certified.

### Technical specifications

Transfer height:	950 mm ± 25 mm*
Colour:	RAL 9002*
Flow direction:	Left to right*
Fixed rail:	Front*
Machine interface:	SMEMA*
Conveyor concept:	ESD belt
Belt speed:	14 m/min.
PCB edge support:	3 mm
Components clearance:	Top 30 mm, bottom 30 mm
Power supply:	230 VAC/50 Hz/1 Ph
Power consumption:	150 VA max.
Air supply:	6 bar
Air consumption:	1.1 ltr/min max.
Machine cycle time:	± 15 seconds
	* or specify

### Options

- Towerlight display
- Alarm buzzer
- Cantilevered input- or output conveyor (length 500 mm)



	<b>NTE 0310IL</b>
Machine dimensions (l x w x h)	653 x 965 x 1300 mm
Weight	110 kg
PCB length	80 mm - 460 mm
PCB width	50 mm - 460 mm
Fixed rail to front dimension (A)	234 mm